

Product Datasheet model i-vo 9160 265



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	<ul style="list-style-type: none">* Duo-spherical lens* Duo component technology* Extremely comfortable for all-day wear* Shock absorbing brow guard* Indirect ventilation* Quattroflex patented temple* Adjustable temple length and lens inclination
Technical details	
Frame	
Material	Front piece TPU/TPE
Colour	blue/orange
Material	Side piece PA
Features	5 position length adjustability
Colour	blue

Material	Temple PBT+PC/TPE
Features	quattroflex temple
Colour	blue/orange
Manufacturer's ID code	Marking W
Applicable EN norm	166
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
No. of certificat. body	0196
Lens	
Material	PC
Thickness	3 mm
Coating	supravisio excellence
Colour	clear
Filter	Marking 2-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperat	T
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE

Miscellaneous

Weight

33 g

Packing

5 spectacles per box

200 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 170