

uvex

**SAFETY
EYEWEAR**

21.09.2015
SBU-E-PGM-PM

Product Datasheet model i-3 9190 315



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	<ul style="list-style-type: none">* Innovative protective spectacle, perfectly fit the face* Individually adjustable side arms with variable inclination* Integrated Softflex zone ensures outstanding wearer comfort for all head sizes* Softflex nose piece ensures comfortable, pressure-free fit and remain firmly in place* Soft ear and Softflex bridge pieces ensure a secure fit in any situation
Technical details Frame Material Features Colour	Front piece/Temple TPU/TPE variable inclination, individually adjustable white-lime

Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact Resistance to high speed particles at extremes of temperat.	F (45 m/s) T
Conformity symbol	CE
No. of certificat. body	0196
Lens	
Material	PC
Thickness	2,2 mm
Coating	supravison excellence
Colour	clear
Marking	
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact Resistance to high speed particles at extremes of temperat.	F (45 m/s) T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE

Miscellaneous

Weight

30 g

Packing

5 spectacles per box

Standards

160 spectacles per cardboard box

DIN EN 166 + DIN EN 170