

uvexSAFETY
EYEWEAR21.09.2015
SBU-E-PGM-PM**Product Datasheet model skyper 9195 075**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth

Product characteristics	<ul style="list-style-type: none">* Ergonomical design* Impact protection up to grade F* Integrated brow, side and cheek guards* Lens replacement possible* Good field of vision* Soft temple end with spring effect* 5 position length adjustability* Adjustable side piece inclination
Technical details	
Frame	
Material	Front piece TPU
Colour	black
Material	Side piece PC
Features	5 position length adjustability
Colour	black

Material	Temple PP
Features	Soft-temple end
Colour	black
Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Tested acc. to DIN	DIN
Conformity symbol	CE
No. of certificat. body	0196
Lens	
Material	PC
Thickness	1,85 mm
Coating	uvex supravision sapphire
Colour	clear
Filter	Marking 2-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Tested acc. to DIN	DIN
Conformity symbol	CE
Miscellaneous	
Weight	31 g
Packing	5 spectacles per box 200 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170