

**Product Datasheet model pheos 9192 080**

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth

**Product  
characteristics**

- \* Modern fashion-look
- \* Duo spherical lens provides excellent all round vision
- \* Eye plus-protection protects the eyebrows through an additional chamfer at the upper range
- \* A slim temple geometry enables a comfortable wearing of earmuffs, helmets and caps
- \* Outstanding ventilation ensures a well eye climate
- \* Temple ends with non-slip components
- \* Eye protection suitable for oil and gas Applications

<b>Technical details</b>	
<b>Frame</b>	
Material	<b>Front piece/Temple</b> POM/TPE
Features	excellent ventilation
Colour	black-grey
<b>Marking</b>	
Manufacturer's ID code	W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Conformity symbol	CE
<b>Lens</b>	
Material	PC
Thickness	2,1 mm
Coating	uvex supravison plus
Colour	clear
<b>Marking</b>	
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
<b>Miscellaneous</b>	
Weight	30 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170