

Product Datasheet model pheos cx2 9198 237

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth

**Product
characteristics**

- * Modern, sportive design with “x”-Brand
- * Comfortable protection due to directly injected forehead and nose pad
- * Innovative uvex duo component technology for maximum wearer comfort
- * Optimal protection due to twist temple technology for a perfect and non-slip fit
- * Duo spherical lens provides a perfect field of vision
- * Excellent ventilation ensures a well eye climate
- * A slim temple geometry enables the combination of the spec with other PPE (earmuffs, helmets and caps)

Technical details**Frame**

Material
Colour

Front piece/Temple

POM/TPE
white, black

Manufacturer's ID code
Applicable EN norm
Low-energy impact
Resistance to high
speed particles at
extremes of temperat.
Conformity symbol

Marking

W
166
F (45 m/s)
T

CE

Lens

Material
Thickness
Coating
Colour

PC
2,2 mm
uvex supravision excellence
grey

Filter
Manufacturer's ID code
Optical class
Low-energy impact
Resistance to high
speed particles at
extremes of temperat.
Surface resistance to
fine particles
Antifog
Conformity symbol

Marking

5-2,5 (DIN EN 172)
W
1
F (45 m/s)
T

K

N
CE

Miscellaneous

Weight

28 g

Packing

5 spectacles per box

160 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 172