

Product Datasheet model ultravision 9301 105**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	<ul style="list-style-type: none">* Anatomical shape and soft material allow close, yet comfortable fit* Fits comfortably over most prescription spectacles* Nose bridge works well with respirators* Frosted top to reduce glare* High-quality, easily adjustable headband* Optically correct lens (EN 166 class 1) does not distort view or cause headaches* Simple lens replacement reduces cost* Chemical resistant outside, antifog inside of lens
Technical details Frame Material Features Colour	Front piece PVC ventilation system transparent light grey

Material	Headband synthetic headband
Features	adjustable
Colour	anthracite/lime
Manufacturer's ID code	Marking W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles) 9 (molten material and hot solids)
Medium-energy impact	B (120 m/s)
Tested acc. to DIN	DIN
No. of certificat. body	0196
Conformity symbol	CE
Lens	
Material	PC
Filter	2,2 mm
Coating	supravision excellence
Colour	clear
Filter	Marking 2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	B (120 m/s)
Field of use	9 (molten material and hot solids)
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE

Miscellaneous

Weight

130 g

Packing

90 pieces in one carton

Standards

DIN EN 166 + DIN EN 170