

**Product Datasheet model polavision 9231.960**



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

|  |   |
|--|---|
| <p><b>Product characteristics</b></p>  | <ul style="list-style-type: none"> <li>• Comfortable twin-lens spectacle</li> <li>• Polarisation filter reliably protects against eye strain</li> <li>• Particularly suitable for reflective surfaces (offshore, maritime conditions)</li> <li>• Protects against reflections and optical irritations outdoors (e. g. water surfaces) for greater visual comfort</li> </ul> |
| <p><b>Technical details</b></p> <p><b>Frame</b></p> <p>Material<br/>Colour</p> <p><b>Material</b><br/>Colour</p> | <p><b>Front piece</b><br/>PC<br/>black mat</p> <p><b>Temple</b><br/>TPR<br/>black</p>   |

|   |                                      |
|---|--------------------------------------|
| Manufacturer's ID code                                      | <b>Marking</b><br>W                  |
| Applicable EN norm  | 166                                  |
| Low-energy impact   | F (45 m/s)                           |
| Resistance to high speed particles at extremes of temperat. | T                                    |
| Conformity symbol   | CE                                   |
| <b>Lens</b>   |                                      |
| Material  | PC                                   |
| Thickness   | 2,1 mm                               |
| Coating   | HC/HC                                |
| Colour  | grey                                 |
| Filter  | <b>Marking</b><br>5-3,1 (DIN EN 172) |
| Manufacturer's ID code                                      | W                                    |
| Optical class   | 1                                    |
| Low-energy impact   | F (45 m/s)                           |
| Resistance to high speed particles at extremes of temperat. | T                                    |
| Conformity symbol   | CE                                   |
| <b>Miscellaneous</b>  |                                      |
| Weight  | 41 g                                 |
| Packing   | 1 spectacle in a retail box          |
| Standards   | DIN EN 166 + DIN EN 172              |