

**Product Datasheet model astrospec 2.0 9164 220**



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

<p><b>Product characteristics</b></p>	<ul style="list-style-type: none"> <li>* Innovative style</li> <li>* Flexible 2K side arms and inclination</li> <li>* Secure and pressure-free fit</li> <li>* Wraparound side arms ensure perfect fit</li> <li>* Ventilation with labyrinth seal helps improve climate around the eyes</li> <li>* Panoramic polycarbonate lens with integrated side protectors for optimum coverage of the eyes</li> <li>* Folds flat</li> </ul>
<p><b>Technical details</b></p> <p><b>Frame</b></p> <p>Material</p> <p>Colour</p> <p>Material</p> <p>Colour</p>	<p><b>Front piece</b></p> <p>PC+TPU</p> <p>black</p> <p><b>Side piece</b></p> <p>POM</p> <p>grey</p>

Material	<b>Temple</b>
Colour	PC+TPU/TPE black-yellow
Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
<b>Lens</b>	
Material	PC
Thickness	2,2 mm
Coating	supravision excellence
Colour	amber
Filter	<b>Marking</b> 2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE

**Miscellaneous**

Weight

37 g

Packing

5 spectacles per box

160 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 170