

**Product Datasheet model 9161 005****UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* Lightweight for prolonged wearing comfort</li><li>* Temple length adjustment</li><li>* Close fit and large lens for unlimited field of vision</li><li>* Fits over most prescription spectacles</li><li>* Anatomically shaped combined with side shields give unsurpassed protection</li><li>* Efficient indirect ventilation incorporated into sidearm design</li><li>* Patented uvex duo-flex temple</li></ul>
<b>Technical details</b>  <b>Frame</b>  Material Features Colour	<b>Side piece</b> PC Indirect ventilation/4 position length adjustability clear

Material	<b>Temple</b> PBT+PC/TPU
Features	Duo-flex temple
Colour	blue/black
Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Conformity symbol	CE
No. of certificat. body	0196
<b>Lens</b>	
Material	PC
Thickness	2,2 mm
Filter	2-1,2 according to DIN EN 170
Coating	uvex supravision sapphire
Colour	clear
Optical class	1
Impact resistance	F (45 m/s) according to DIN EN 166
Filter	<b>Marking</b> 2C-1,2 ( DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Conformity symbol	CE
<b>Miscellaneous</b>	
Weight	47 g
Packing	75 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170