

**Product Datasheet model ultravision 9301 714**

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* Anatomical shape and soft material allow close, yet comfortable fit</li><li>* Fits comfortably over most prescription spectacles</li><li>* Nose bridge works well with respirators</li><li>* Frosted top to reduce glare</li><li>* High-quality, easily adjustable headband</li><li>* Optically correct lens (EN 166 class 1) does not distort view or cause headaches</li><li>* Simple lens replacement reduces cost</li></ul>
<b>Technical details</b>	
<b>Frame</b>	<b>Front piece</b>
Material	PVC
Features	ventilation system
Colour	transparent light grey

Material	<b>Headband</b>
Features	synthetic headband
Colour	adjustable anthracite/lime
Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Impact resistance	F (45 m/s)
Tested acc. to DIN	DIN
No. of certificat. body	0196
Conformity symbol	CE
<b>Lens</b>	
Material	CA
Thickness	1,2 mm
Coating	inside antifog
Colour	clear
Filter	<b>Marking</b> 2-1,2 ( DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Impact resistance	F (45 m/s)
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE

**Miscellaneous**

Weight

119 g

Packing

80 pieces in one carton

Standards

DIN EN 166 + DIN EN 170