

Product Datasheet model astrospec 2.0 9164 246



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

<p>Product characteristics</p>	<ul style="list-style-type: none"> * Innovative style * Flexible 2K side arms and inclination * Secure and pressure-free fit * Wraparound side arms ensure perfect fit * Ventilation with labyrinth seal helps improve climate around the eyes * Panoramic polycarbonate lens with integrated side protectors for optimum coverage of the eyes * Folds flat
<p>Technical details</p> <p>Frame</p> <p>Material Colour</p> <p>Material Colour</p>	<p>Front piece PC+TPU neonorange</p> <p>Side piece POM grey</p>

Material	Temple
Colour	PC+TPU/TPE neonorange-black
Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
Lens	
Material	PC
Thickness	2,2 mm
Coating	supravisision excellence
Colour	grey
Filter	Marking 5-2,5 (DIN EN 172)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE

Miscellaneous

Weight

37 g

Packing

5 spectacles per box

160 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 172