

Product Datasheet model astrospec 2.0 9164 187

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth

**Product
characteristics**

- * Innovative style
- * Flexible 2K side arms and inclination
- * Secure and pressure-free fit
- * Wraparound side arms ensure perfect fit
- * Ventilation with labyrinth seal helps improve climate around the eyes
- * Panoramic polycarbonate lens with integrated side protectors for optimum coverage of the eyes
- * Folds flat
- * Eye protection suitable for oil and gas applications

Technical details

Frame

Material
Colour

Front piece

PC+TPU
black

Material
Colour

Side piece

POM
grey

Material
Colour

Temple

PC+TPU/TPE
black-grey

Manufacturer's ID code
Applicable EN norm
Low-energy impact
Resistance to high
speed particles at
extremes of temperat.
Conformity symbol

Marking

W
166
F (45 m/s)
T

CE

Lens	
Material	PC
Thickness	2,2 mm
Coating	uvex supravision plus
Colour	clear
Marking	
Filter	2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Miscellaneous	
Weight	37 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170