

Product Datasheet model skyguard NT 9175 275**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	<ul style="list-style-type: none">* An improved spectacle with all-round protection* An injection moulded TPU frame increase Wearer protection levels through minimising the risk of particle ingress* The flexible, closed-pore soft components enables a customised, individual fit* Easy to clean to promote long term use* Individual side arm inclination
Technical details	
Frame	
Material	Front piece PP
Colour	grey
Material	TPU layer TPU
Colour	orange

Manufacturer's ID code	Marking W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Low-energy impact	F (45 m/s)
Conformity symbol	CE
Material	Side piece PBT+PC
Features	adjustable inclination
Colour	grey
Material	Temple PBT+PC
Colour	grey
Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45m/s)
Tested acc. to DIN	DIN
Conformity symbol	CE
No. of certificate. body	0196
Lens	
Material	PC
Thickness	2,1 mm
Coating	supravision excellence
Colour	clear

	Marking
Filter	2-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE
Miscellaneous	
Weight	43 g
Packing	5 spectacles 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170