

Product Datasheet model i-vo 9160 041**UVEX ARBEITSSCHUTZ GMBH,
Würzburger Str. 181-189, D-90766 Fürth**

| | |
|--------------------------------|--|
| Product characteristics | <ul style="list-style-type: none">* Duo-spherical lens* Duo component technology* Extremely comfortable for all-day wear* Shock absorbing brow guard* Indirect ventilation* Quattroflex patented temple* Adjustable temple length and lens inclination* Grey lens tint ensures perfect colour recognition |
| Technical details | |
| Frame | Front piece |
| Material | TPU/TPE |
| Colour | black/green |
| | Side piece |
| Material | PC |
| Features | length adjustability |
| Colour | black |

| | |
|--|-----------------------------------|
| Material | Temple |
| Features | TPU/TPE |
| Colour | quattroflex temple black/green |
| Manufacturer's ID code | Marking |
| Applicable EN norm | W |
| Low-energy impact | 166 |
| Resistance to high speed particles at extremes of temperatures | F (45 m/s) |
| Conformity symbol | T |
| No. of certificat. Body | CE 0196 |
| Lens | |
| Material | PC |
| Thickness | 3 mm |
| Coating | infradur plus |
| Colour | grey |
| Filter | Marking |
| Manufacturer's ID code | 1,7 (DIN EN 169) |
| Optical class | W |
| Low-energy impact | 1 |
| Resistance to high speed particles at extremes of temperatures | F (45 m/s) |
| Surface resistance to fine particles | T |
| Antifog | K |
| Conformity symbol | N CE |

Miscellaneous

Weight

33 g

Packing

5 spectacles per box

200 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 169